arXiv:0810.1888v2 [physics.flu-dyn] 15 Oct 2008

Dynamics of Water Entry

Tadd T. Truscott[1], Jeffrey M. Aristoff[2], &
Alexandra H. Techet[1]

[1]Department of Mechanical Engineering, Massachusetts Institute of Technology
Cambridge, MA 02139 USA
[2]Department of Mathematics, Massachusetts Institute of Technology
Cambridge, MA 02139 USA

October 15, 2008

Abstract

The hydrodynamics associated with water-entry of spheres can be highly variable with respect to the material and kinematic properties of the sphere. This series of five fluid dynamics videos illustrates several subtle but interesting variations that can be seen. The first series of videos contrasts the nature of impact ($Fr = U_o/\sqrt{gd} = 5.15$) between a hydrophilic (wetting angle of $\alpha = 60°$) and hydrophobic sphere ($\alpha = 120°$), and illustrates how surface coating can affect whether or not an air cavity is formed; the views from the side and from above are synchronized in time. The second video series illustrates how spin and surface treatments can alter the splash and cavity formation following water entry. The spinning sphere ($S = \omega r/U_o = 1.7$; $Fr = 5.15$) causes a wedge of fluid to be drawn into the cavity due to the no-slip condition and follows a curved trajectory. The non-spinning sphere ($Fr = 5.15$) has two distinct surface treatments on the left and right hemispheres: the left hemisphere is hydrophobic ($\alpha = 120°$) and the right hemisphere is hydrophilic ($\alpha = 60°$). Interestingly, the cavity formation for the half-and-half sphere has many similarities to that of the spinning sphere especially when viewed from above. The third video series compares two millimetric nylon spheres impacting at slightly different impact speeds ($U_o = 40cm/s$ and $U_o = 45cm/s$); the faster sphere fully penetrates the free surface, forming a cavity, whereas the slower sphere does not. The fourth series shows the instability of an elongated water-entry cavity formed by a millimetric steel sphere with a hydrophobic coating impacting at $U_o = 600cm/s$. The elongated cavity forms multiple pinch-off points along its decent.

1 Information

Two sample videos are (Video 1 mpeg-1) and (Video 2 mpeg-2).

2 References

Aristoff, J.M. & Bush, J.W.M. "Water Entry of Small Hydrophobic Spheres." *J Fluid Mech.* In press 2008.

Truscott, T.T. & Techet, A.H. "Water-Entry of Spinning Spheres." *J Fluid Mech.* Under Review 2008.

Aristoff, J.M., Truscott, T.T., Techet, A.H. & Bush, J.W.M. "The Life of a Water-Entry Cavity at Low Bond Number." *Physics of Fluids*, September 2008.

Truscott, T.T. & Techet, A.H. "Cavity Formation in the Wake of a Spinning Sphere Impacting the Free Surface," *Physics of Fluids*, v. 18, no. 9, p. 18, cover, and inset, September 2006.